Distributed by:

JAMECO® ELECTRONICS

www.Jameco.com ✦ 1-800-831-4242

The content and copyrights of the attached material are the property of its owner.

SPECIFICATION SHEET

DATE: JUN.24,99'.
NO.: HN99062405
PAGE: 1/2

TYPE: HN-27GB TYPE
MODEL: HN-GH12-0953Y
CUSTOMER PART NO.:

Jameco Part Number 167038

I. OUTER DIMENSIONS :



II.GEAR RATIO : 188:1

TYPE	A	B	C	D	E	F
RATIO	10	21	43	90	188	392
DIM "L" MM	14.5	14.5	19.5	19.5	24.5	24.5
EFF %	81	73	73	66	59	59
ALLOWABLE TORQUE Kg-cm	0.15	0.25	0.4	0.8	1.4	2

SPECIFICATION SHEET

DATE: JUN.24,99'.
NO.: HN99062405
PAGE: 2/2

TYPE: HN-HN27GB TYPE
MODEL NO.: HN-GH12-0953Y
CUSTOMER PART NO.:

III. SPECIFICATIONS :

1. RATED VOLTAGE: DC 12V

2. DC VOLTAGE OPERATING RANGE: DC 4.5-24V

3. TORQUE (LOAD) AT MAXIMUM EFFICIENCY : 1.20 Kg-cm

4. NO LOAD SPEED: 14 RPM +/-10%

5. SPEED AT MAXIMUN EFFICIENCY (UNDER LOAD AT 1.20 Kg-cm): 9 RPM +/- 10%

6. NO LOAD CURRENT: MAX. 45 mA

7. CURRENT AT MAX. EFFICIENCY (UNDER LOAD AT 1.20 Kg-cm): MAX. 90 mA

8. SHAFT END PLAY: 0.8 m/m

9. INSULATION RESISTANCE: 10M OHM

10. DIELECTRIC STRENGTH: 300V DC

11. GEAR RATIO : 188:1